

XTravelSystem Web Service. Transfer Handler

Date revision: 20240423

Contents

XTravelSystem Web Service. Transfer Handler	1
DESCRIPTION	2
TEST ENVIRONMENT ACCESS	2
GENERAL CONDITIONS	2
METHODS	2
getTransferEstablishments	2
getTransferZones	4
getTransferAirports	5
getCountriesByAgency	6
availableTransfersV14	6
valuateV14	14
confirmV14	24

DESCRIPTION

This document includes the description of all the methods to handle transfer booking operations: availability and confirm operations.

In the file MAN_xts_WSClientSpec_en_base you will find a group of tips and recommendations for the correct use of our API that must be reviewed before carrying out any development.

We work with an online, stateless system, so the product received may change at any time. Also, some suppliers return illustrative prices/cancellation terms at availability. That's why we strongly recommend the use of the Valuate message to ensure the results.

Our API also allows search requests and confirmations by ZONE, however, for a correct use of the API it is mandatory that bookings are made by HOTEL, for the whole booking flow (availability-valuate-confirm). It is for this reason that only requests per HOTEL will be certified and be valid after LIVE certification.

Another important aspect to take into account when developing the API of transfers is that the information of FLIGHT is mandatory to be sent, to avoid operation issues when transfer driver collect customers at the pickup point. This info must be sent in the Confirm step.

TEST ENVIRONMENT ACCESS

WSDL: https://live.easytravelsystem.com/public/v1_0rc1/transferBookingHandler?WSDL

Endpoint: https://live.easytravelsystem.com/public/v1_0rc1/transferBookingHandler

GENERAL CONDITIONS

The dates have this format: YYYY-MM-DDTHH24:MM:SS. Example: 2018-11-02T12:00:00

To avoid problems with different time zones always use the time format as

YYYY-MM-DDT**12:00:00**

METHODS

getTransferEstablishments

Returns a list of hotels with available transfers.

getTransferEstablishments Request

agencyCode (required)	Agency code. Unique code for each customer.
brandCode (required)	Brand code. Same code for all methods.
pointOfSaleId (required)	Point of Sale. Same code for all methods.

airportCode	Airport code. See <i>commonsHandler:getAirports.</i> (send either airportCode, areaCode, cityCode)
areaCode	Area code. See <i>commonsHandler:getAreas.</i> (send either airportCode, areaCode, cityCode)
cityCode	Area code. See <i>commonsHandler:getCities..</i> (send either airportCode, areaCode, cityCode)
fromRow	From row number.
language	Response language.
numRows	Row number.
searchName	Hotel name (or partial name).

getTransferEstablishments Response

result	Result item. Composed of:	
	address	Address of Establishment
	address	Street and Number.
	cityCode	City Code of Establishment.
	cityName	City Name of Establishment.
	countryCode	Country Code of Establishment.
	countryName	Country Name of Establishment.
	email	E-Mail of Establishment.
	fax	Fax of Establishment.
	stateCode	State Code of Establishment.
	stateName	State Name of Establishment.

		telephone	Telephone of Establishment.
		zipCode	Zip Code of Establishment.
		categoryName	Category name.
		establishmentId	Establishment code.
		establishmentName	Establishment name.

getTransferZones

Returns a list of Zones with available transfers.

getTransferZones Request

agencyCode (required)	Agency code. Unique code for each customer.
brandCode (required)	Brand code. Same code for all methods.
pointOfSaleId (required)	Point of Sale. Same code for all methods.
airportCode	Airport code. See <i>commonsHandler:getAirports.</i> (send either airportCode, areaCode, cityCode)
areaCode	Area code. See <i>commonsHandler:getAreas.</i> (send either airportCode, areaCode, cityCode)
cityCode	Area code. See <i>commonsHandler:getCities..</i> (send either airportCode, areaCode, cityCode)
language	Response language.

getTransferZones Response

result		Result item. Composed of:
	zoneId	Zone ID.
	zoneName	Zone name.

getTransferAirports

Returns a list of airports with available transfers.

getTransferAirports Request

agencyCode (required)	Agency code. Unique code for each customer.
brandCode (required)	Brand code. Same code for all methods.
pointOfSaleId (required)	Point of Sale. Same code for all methods.
countryCode	Airport code. See <i>commonsHandler:getCountries</i> .
language	Response language.

getTransferAirports Response

airports	Airport item, composed of:
code	Airport code.
iataCode	IATA code (If airport type is AIR).
name	Airport name.
type	Airport type. Values: <ul style="list-style-type: none"> - AIR - SEA - LAND

getCountriesByAgency

Returns a list of Countries with available transfers for a given agency.

getCountriesByAgency Request

agencyCode (required)	Agency code. Unique code for each customer.
brandCode (required)	Brand code. Same code for all methods.
pointOfSaleId (required)	Point of Sale. Same code for all methods.
language	Response language.

getCountriesByAgency Response

list	Country item, composed of:
code	Country code.
name	Country name.

availableTransfersV14

Retrieves available transfers for a given route. Able to searchTransfer By ZONE or by HOTEL, however use only option by HOTEL, rather than by ZONE.

availableTransfersV14 Request

agencyCode (required)	Agency code. Unique code for each customer.
brandCode (required)	Brand code. Same code for all methods.

pointOfSaleId (required)	Point of Sale. Same code for all methods.
adults	Number of adults.
children	Number of children.
childrenAges	Send one item per child. A childrenAges is required for each child. None is required if children = 0.
fromAirToHotelJourney (required if journeyDirection value = Going or Roundtrip)	<p>Air to hotel journey details:</p> <ul style="list-style-type: none"> - airportId: transfer airport departure code. Transfer departure site. See method getTransferAirports. - establishmentId: transfer destination. See method getTransferEstablishments. - flightInfo. Flight and transfer Information, composed of: <ul style="list-style-type: none"> flightNumber. Flight number, composed of: <ol style="list-style-type: none"> 1. company: either the IATA or IACO code (example: British Airways codes are BA or BAW) 2. number: flight number (usually a 3 or 4 digit integer) 3. fullNumber: flight number in full. Optional. This tag will be mandatory on confirm request. date: flight arrival date. Note that it is required to send the arrival date here, not the departure date. This date will be used for transfer collection day. from: Departure airport. IATA code (optional). localtime: Local time. Note that it is required to send the arrival time (same time which is received from Airline) here, not the departure time. This time will be used for transfer collection time. to: Arrival airport. IATA code (optional and should be the same airport as airportId)

fromHotelToAirJourney (required if journeyDirection value = Return or Roundtrip)	Hotel to Air journey details: 1. airportId : transferairport destination code. Transfer destination. See method getTransferAirports . 2. establishmentId : transfer departure site. See method getTransferEstablishments . 3. flightInfo . Flight and transfer Information, composed of: flightNumber . Flight number, composed of: 1. company : either the IATA or IACO code (example, for British Airways: BA or BAW). 2. number : flight number (usually a 3 or 4 digit integer) 3. fullNumber : flight number in full. Optional. This tag will be mandatory on confirm request. date : flight departure date. Note that it is required to send the departure date here, not the arrival date. This date will be used for transfer collection day. from : Departure airport. IATA code (optional and should be the same airport as airportId) localtime : Local time. Note that it is required to send the departure time (same time which is received from Airline) here, not the arrival time. This time will be used for transfer collection time. to : Arrival airport. IATA code (optional).
fromRow	Results will be sent from this row.
journeyDirection (required)	Requested journey direction (values are case sensitive): <ul style="list-style-type: none"> - Going: from airport to hotel. - Return: from hotel to airport. - Roundtrip (2 trips): from airport to hotel and from hotel to airport.
language (required)	Language sent in the response.
numRows (required)	Total number of rows requested (each row is a search result). Minimum value: 1.
fromAirToZoneJourney (required if journeyDirection value = Going or Roundtrip)	Please, don't use this option per ZONE.

fromZoneToAirJourney (required if journeyDirection value = Going or Roundtrip)	Please, don't use this option per ZONE.
--	---

availableTransfersV14 Response

adults	Number of adults
children	Number of children
childrenAges	One item per child.
fromAirToZoneJourney	xsi:nil="1" (when search method is By Hotel ID)
fromZoneToAirJourney	xsi:nil="1" (when search method is By Hotel ID)
journeyDirection	Requested journey direction. Values: <ul style="list-style-type: none"> - Going: from airport to hotel. - Return: from hotel to airport. - Roundtrip (2 trips): from airport to hotel and from hotel to airport.
transferOption	An option for the requested transfer. From 1 to n items in this response.
	Direction Journey direction. Values: <ul style="list-style-type: none"> - Going: from airport to hotel. - Return: from hotel to airport. - Roundtrip (2 trips): from airport to hotel and from hotel to airport.
	locationTextGoing Important information: available assistance if any, collection procedure, etc. Relevant for the Going transfer.
	locationTextReturn Important information: available assistance if any, collection procedure, etc. Relevant for the Return transfer.
	numVehicles Number of Vehicles for this option when serviceType is Private. Zero when serviceType is Shuttle or Speedy Shuttle.
	price Transfer option price information object.
	paxPrice Price per pax for this transfer option

		currencyCode	Currency code
		value	Amount per pax
		priceType	Price type. Values: - PAX: price per pax - VEHICLE: price per vehicle.
		supplement	Supplementobject. From 0 to n. Required supplements already included in price.
		currencyCode	Currency code
		description	Supplement description
		value	Amount
		total	Total transfer price.
		currencyCode	Currency code
		value	Total transfer amount, including supplements.
		unitPrice	Price information object. From 1 to 2 items. Depends on priceType
		currencyCode	Currency code
		value	Amount per unit.
		paxType	Unit price type. Values: - Vehicle: in case this is a per vehicle price (Private transfers) - Pax: in case this is a per pax price (Shuttle transfers)
		serviceType	Service type. Values: - Private: Private vehicle transfer - Shuttle: shared vehicle transfer - Speedy Shuttle: shared vehicle transfer with less stops than a conventional transfer.
		vehicleInfo	Vehicle information

			carId	Vehicle code.		
			carName	Vehiclename.		
			description	Vehicle description.		
			imageUrl	Vehicle image url.		
			numPassenger	Vehicle max capacity.		
	Comments		Miscellaneous comments.			
		Text	The value itself. See next note.			
fromAirToHotelJourney				Air to Zone journey details as requested. Composed of:		
			airportId	Transfer departure site. An airport code.		
			establishmentId	Transfer destination. A hotel code if sent in request, in adverse case field will be return empty		
			flightInfo	Flight and transfer data, composed of:		
			date	Transfer departure date.		
				flightNumber	Flight number, composed of:	
				company	Either the IATA or IACO code.	
					fullNumber	Flight number in full.
					number	Flight number.
			from	Departure airport.		
			localTime	Transfer departure time (time of TimeZone local)		
			to	Arrival airport.		
	zoneld	Transfer departure site. An Zone code				

fromHotelToAirJourney		Zone to Air journey details as requested. Composed of::	
	airportId		Transfer destination site. An airport code.
	establishmentId		Transfer destination. A hotel code if sent in request, in adverse case field will be return empty.
	flightInfo		Flight and transfer data, composed of:
		date	Transfer departure date.
		flightNumber	Flight number, composed of:
		company	Either the IATA or IACO code.
		fullNumber	Flight number in full.
		number	Flight number.
		from	Departure airport.
		localTime	Transfer departure time (time of TimeZone local)
		to	Arrival airport.
	zoneId		Transfer departure site. A Zone code
		Type	<p>Comment type. Values:</p> <ul style="list-style-type: none"> - “ Cancellation term “ : cancellation terms <u>by transfer</u>. The format is as follows: [Release – Percent%]. <p>For example: 7 – 5.0% , means cancelling a booking from 7 days before checkin date has a 5.0% of total booking amount penalty.</p> <p>Note: it is not possible to cancel a transfer online with a 100% percent penalty release (when it applies). You have to do it using the email, be aware of the fact the <u>booking cancellation request will remain “on request” and it is not confirmed</u>. Our staff will deal with it manually and contact your booking staff to confirm cancellation terms.</p> <ul style="list-style-type: none"> - “ Cancellation email “ : email to request a manual booking cancellation, useful when having a 100% cancellation penalty, see previous note. - “Sales Commission percent” : Commission applied - “Sales Commission amount” : Amount of the previous percent applied to the transfer price.
fromRow		Results search data: from row number.	

numRows	Results search data: row number.
totalRows	Results search data: total row number.

valuateV14

Valuates available transfer options for a given route. Able to ValauteTransfer by HOTEL or by ZONE; however use only option by HOTEL, rather than by ZONE.

valuateV14 Request

agencyCode(required)	Agency code. Unique code for each customer.
brandCode(required)	Brand code. Same code for all methods.
pointOfSaleId(required)	Point of Sale. Same code for all methods.
fromAirToHotelJourney (required if journeyDirection value = Going or Roundtrip)	<p>Air to hotel journey details:</p> <ul style="list-style-type: none"> - airportId: transfer airport departure code. Transfer departure site. See method getTransferAirports. - establishmentId: transfer destination. See method getTransferEstablishments. - flightInfo. Flight and transfer Information, composed of: flightNumber. Flight number, composed of: <ol style="list-style-type: none"> 1. company: either the IATA or IACO code (example: British Airways codes are BA or BAW) 2. number: flight number (usually a 3 or 4 digit integer) 3. fullNumber: flight number in full. Optional. This tag will be mandatory on confirm request. <p>date: flight arrival date. Note that it is required to send the arrival date here, not the departure date. This date will be used for transfer collection day.</p> <p>from: Departure airport. IATA code (optional).</p> <p>localtime: Local time. Note that it is required to send the arrival time (same time which is received from Airline) here, not the departure time. This time will be used for transfer collection time.</p> <p>to: Arrival airport. IATA code (optional and should be the same airport as airportId)</p>

fromHotelToAirJourney (required if journeyDirection value = Return or Roundtrip)	Hotel to Air journey details: <ul style="list-style-type: none"> - airportId: transferairport destination code. Transfer destination. See method <i>getTransferAirports</i>. - establishmentId: transfer departure site. See method <i>getTransferEstablishments</i>. - flightInfo. Flight and transfer Information, composed of: flightNumber. Flight number, composed of: <ol style="list-style-type: none"> 1. company: either the IATA or IACO code (example, for British Airways: BA or BAW). 2. number: flight number (usually a 3 or 4 digit integer) 3. fullNumber: flight number in full. Optional. This tag will be mandatory on confirm request. <p>date: flight departure date. Note that it is required to send the departure date here, not the arrival date. This date will be used for transfer collection day.</p> <p>from: Departure airport. IATA code (optional and should be the same airport as airportId)</p> <p>localtime: Local time. Note that it is required to send the departure time (same time which is received from Airline) here, not the arrival time. This time will be used for transfer collection time.</p> <p>to: Arrival airport. IATA code (optional).</p>
journeyDirection (required)	Requested journey direction (values are case sensitive): <ul style="list-style-type: none"> - Going: from airport to hotel. - Return: from hotel to airport. - Roundtrip: (2 trips): from airport to hotel and from hotel to airport.
language (required)	Language sent in the response.
supplements	not in use

vehicleOccupancy (required)	<p>Vehicle occupancy data. Send from 1 to n items</p> <ul style="list-style-type: none"> - adults: Number of adults - children: Number of children - [childrenAges]: children ages. One item per child. - journeyDirection: Requested journey direction. <ul style="list-style-type: none"> - Going: from airport to hotel. - Return: from hotel to airport. - Roundtrip (2 trips): from airport to hotel and from hotel to airport. - [names]: Passenger names (optional) several can be sent. - numberOfVehicles: Number of vehicles to be valuated (only in case of serviceType = Private) - [optionalSupplement]: Supplement information - quantity: Quantity of this Supplement. - supplementCode: Code of this Supplement. - serviceType: Service type. Values: <ul style="list-style-type: none"> - Private - Shuttle - Speedy Shuttle - vehicleTypeId: vehicle type Id. Mandatory for serviceType Private
fromAirToZoneJourney (required if journeyDirection value = Going or Roundtrip)	Please, don't use this option per ZONE.
fromZoneToAirJourney (required if journeyDirection value = Return or Roundtrip)	Please, don't use this option per ZONE.

valuateV14 Response

amount	not in use.
commission	not in use.
date	not in use.

status		not in use.	
fromAirToHotelJourney		Air to Hotel journey details as requested. Composed of:	
		airportId	Transfer departure site. An airport code.
		establishmentId	Transfer destination. A hotel code. (will be empty if not sent in request)
		flightInfo	Flight and transfer data, composed of:
		date	Transfer departure date.
		flightNumber	Flight number, composed of:
		company	Either the IATA or IACO code.
		fullNumber	Flight number in full.
		number	Flight number.
	from		Departure airport.
	localtime		Transfer departure time.
	to		Arrival airport.
fromHotelToAirJourney		Zone to Air journey details as requested. Composed of:	
		airportId	Transfer destination site. An airport code.
		establishmentId	Transfer departure site. A hotel code. (will be empty if not sent in request)
		flightInfo	Flight and transfer data, composed of:
		date	Transfer departure date/time.
		flightNumber	Flight number, composed of:
		company	Either the IATA or IACO code.

			fullNumber	Flight number in full.
			number	Flight number.
			from	Departure airport.
		localtime	Transfer departure time.	
		to	Arrival airport.	
journeyDirection			Requested journey direction. Values: <ul style="list-style-type: none">- Going: from airport to hotel.- Return: from hotel to airport.- Roundtrip (2 trips): from airport to hotel and from hotel to airport.	
totalPaxes			Total number of paxes as requested.	
		adults	Number of adults.	
		children	Number of children.	
totalPrice			Total transfer price.	
		currencyCode	Currency code.	
		value	Total amount.	
transferOption			Details for requested transfer valuation.	
	Direction		Journey direction. Values: <ul style="list-style-type: none">- Going: from airport to hotel.- Return: from hotel to airport.- Roundtrip (2 trips): from airport to hotel and from hotel to airport.	
	locationTextGoing		Important information: available assistance if any, collection procedure, etc. Relevant for the Going transfer.	
	locationTextReturn		Important information: available assistance if any, collection procedure, etc Relevant for the Return transfer.	
	numVehicles		Total Number of Vehicles	

	price		Transfer option price information object.
	paxPrice		Price per pax for this transfer option
		currencyCode	Currency code
		value	Amount per pax
	priceType		Price type. Values: <ul style="list-style-type: none"> - PAX: price per pax - VEHICLE: price per vehicle.
	unitPrice		Price information object. From 1 to 2 items. Depends on priceType
		currencyCode	Currency code
		value	Amount per unit
		paxType	Unit price type. Values: <ul style="list-style-type: none"> - Vehicle: in case this is a per vehicle price (Private transfers) - Pax: in case this is a per pax price (Shuttle transfers)
	serviceType		Service type. Values: <ul style="list-style-type: none"> - Private: Private vehicle transfer - Shuttle: shared vehicle transfer - Speedy Shuttle: shared vehicle transfer with less stops than a conventional transfer.
	vehicleInfo		Vehicle information
		carId	Vehicle code
		carName	Vehiclename
		description	Vehicle description
		imageUrl	Vehicle image URL
		numPassenger	Vehicle max capacity
	adults		Number of adults.
	children		Number of children.
	childrenAges		Ages of Children.

			names	Pax names as requested.
			Comments	Miscellaneous comments.
			Text	The value itself. See next note.
			Type	<p>Comment type. Values:</p> <ul style="list-style-type: none">- “ Cancellation term “ : cancellation terms <u>by transfer</u>. The format is as follows: [Release – Percent%]. <p>For example: 7 – 5.0% , means cancelling a booking from 7 days before checkin date has a 5.0% of total booking amount penalty.</p> <p>Note: it is not possible to cancel a transfer online with a 100% percent penalty release (when it applies). You have to do it using the email, be aware of the fact the <u>booking cancellation request will remain “on request” and it is not confirmed</u>. Our staff will deal with it manually and contact your booking staff to confirm cancellation terms.</p> <ul style="list-style-type: none">- “ Cancellation email “ : email to request a manual booking cancellation, useful when having a 100% cancellation penalty, see previous note.- “Sales Commission percent” : Commission applied- “Sales Commission amount” : Amount of the previous percent applied to the transfer price.
fromAirToZoneJourney			xsi:nil="1" (when search method is By Zone ID)	
fromZoneToAirJourney			xsi:nil="1" (when search method is By Zone ID)	

confirmV14

Confirms a transfer booking. Able to ConfirmTransfer By HOTEL or by ZONE, however this last option must not be used.

confirmV14 Request

Please see below Request when using search method Transfer By HOTEL (Not included request tags **fromAirToZoneJourney** and **fromZoneToAirJourney** as this option must not be used).

agencyCode (required)	Agency code. Unique code for each customer.
brandCode (required)	Brand code. Same code for all methods.
pointOfSaleId (required)	Point of Sale. Same code for all methods.
fromAirToHotelJourney (required if journeyDirection value = Going or Roundtrip)	Air to hotel journey details: <ul style="list-style-type: none"> - airportId: transfer airport departure code. Transfer departure site. See method getTransferAirports. - establishmentId: transfer destination. See method getTransferEstablishments. - flightInfo. Flight and transfer Information, composed of: flightNumber. This information is mandatory to send in the step of Confirmation Flight number, composed of: <ol style="list-style-type: none"> 1. company: either the IATA or IACO code (example: British Airways codes are BA or BAW) 2. number: flight number (usually a 3 or 4 digit integer) 3. fullNumber: flight number in full. Mandatory. This tag is used by transporter to check real flight departure/arrival time. <p>date: flight arrival date. Note that it is required to send the arrival date here, not the departure date. This date will be used for transfer collection day.</p> <p>from: Departure airport. IATA code (optional).</p> <p>localtime: Local time. Note that it is required to send the arrival time (same time which is received from Airline) here, not the departure time. This time will be used for transfer collection time.</p> <p>to: Arrival airport. IATA code (optional and should be the same airport as airportId)</p>

<p>fromHotelToAirJourney (required if journeyDirection value = Return or Roundtrip)</p>	<p>Hotel to Air journey details:</p> <ul style="list-style-type: none"> - airportId: transferairport destination code. Transfer destination. See method <i>getTransferAirports</i>. - establishmentId: transfer departure site. See method <i>getTransferEstablishments</i>. - flightInfo. Flight and transfer Information, composed of: <ul style="list-style-type: none"> flightNumber. Flight number, composed of: <ol style="list-style-type: none"> 1. company: either the IATA or IACO code (example, for British Airways: BA or BAW). 2. number: flight number (usually a 3 or 4 digit integer) 3. fullNumber: flight number in full. Mandatory. This tag is used by transporter to check real flight departure/arrival time. <p>date: flight departure date. Note that it is required to send the departure date here, not the arrival date. This date will be used for transfer collection day.</p> <p>from: Departure airport. IATA code (optional and should be the same airport as airportId)</p> <p>localtime: Local time. Note that it is required to send the departure time (same time which is received from Airline) here, not the arrival time. This time will be used for transfer collection time.</p> <p>to: Arrival airport. IATA code (optional).</p>
<p>journeyDirection(required)</p>	<p>Requested journey direction (values are case sensitive):</p> <ul style="list-style-type: none"> - Going: from airport to hotel. - Return: from hotel to airport. - Roundtrip (2 trips): from airport to hotel and from hotel to airport.
<p>language (required)</p>	<p>Language sent in the response.</p>
<p>supplements</p>	<p>Not in use</p>

vehicleOccupancy (required)	<p>Vehicle occupancy data. Send from 1 to n items</p> <ul style="list-style-type: none"> - adults: Number of adults - children: Number of children - [childrenAges]: children ages. One item per child. - journeyDirection: requested journey direction. <ul style="list-style-type: none"> - Going: from airport to hotel. - Return: from hotel to airport. - Roundtrip (2 trips): from airport to hotel and from hotel to airport. - [names]: Passenger names (optional) several can be sent. - numberOfVehicles: Number of vehicles to be valued (only in case of serviceType = Private) - [optionalSupplement]: Supplement information - quantity: Quantity of this Supplement. - supplementCode: Code of this Supplement. - serviceType: Service type. Values: <ul style="list-style-type: none"> - Private - Shuttle - Speedy Shuttle - vehicleTypeId: vehicle type Id. Mandatory for serviceType Private
agencyReference	<p>Customers reference (locator) for this booking. Free text. It is mandatory to send the client's agencyReference in confirmation.</p>
basketId	<p>Basket code. An existing XTS basketId or a null value. If it is not specified, XTS will assign one basketId automatically. In any case the response object will return it.</p>
closeBasket	<p>Boolean. Values (By default: True):</p> <ul style="list-style-type: none"> - FALSE: this basket is open. It must be closed later with basketHandler confirm method or, either be canceled with basketHandler cancel method - TRUE: this basket is closed, documentation is sent, transfer provider receives booking confirmation, invoicing process is started.

comments (required)	<p>An array: at least one booking comment should be sent, including the following information:</p> <ul style="list-style-type: none"> - type : comment type (mandatory). CLIENT. - text : comment text (mandatory). Destination information, such as, Hotel name, Point of Interest or Postal Address. <p>Besides, other comments you may consider necessary can be also included. In the same array structure:</p> <ul style="list-style-type: none"> - type : comment type (mandatory). CLIENT. - text : comment text (mandatory). Free text.
sendVoucher	<p>Boolean. Values:</p> <ul style="list-style-type: none"> - FALSE: do not send voucher - TRUE: send voucher.
Titular (required)	Main pax name.
userId	User code of the agency. You can use it as a search param in the getBaskets method
voucherEmail	E-mail address where voucher has to be sent.
fromAirToZoneJourney (required if journeyDirection value = Going or Roundtrip)	Please, don't use this option per ZONE.
fromZoneToAirJourney (required if journeyDirection value = Return or Roundtrip)	Please, don't use this option per ZONE.

confirmV14 Response

basket	Basket data
basketId	Basket code
cancelled	Cancel data. Always set to 0.
closed	Closed data

			opened		Opened data							
			titular		Main pax name.							
confirmService					One for each journey. Composed of:							
			journeyDirection		Values: <div>- Going. - Return.</div>							
			serviceId		Service code.							
			transferJourney		Transfer data. Composed of:							
					airportId		Transfer departure site. An airport code.					
					establishmentId		Transfer destination. A hotel code.					
					flightInfo		Flight and transfer data, composed of:					
							date		Transfer departure date.			
							flightNumber		Flight number, composed of:			
									company		Either the IATA or IACO code.	
									fullNumber		Flight number in full.	
									number		Flight number.	
					from		Departure airport.					
					localTime		Local Time.					
			to		Arrival airport.							
			zoneId		Transfer departure site. A Zone code							
			vehicleOccupancy					Vehicle Occupancy data. From 1 to n items. Composed of:				
					adults		Number of adults.					

			children	Number of children.
			childrenAge	Age of Children.
			journeyDirection	Not in use.
			names	Pax names as requested.
			numberOfVehicles	Number of vehicles assigned (If transfer is Private).
			serviceType	Service type. Values: <ul style="list-style-type: none">- Private: Private vehicle transfer- Shuttle: shared vehicle transfer- Speedy Shuttle: shared vehicle transfer with less stops than a conventional transfer.
			vehicleTypeId	Vehicle type code
			locationTextGoing	In case of Going transfer: Important information for transfer: collection procedure, etc.
			locationTextReturn	In case of Return transfer: Important information for transfer: collection procedure, etc.
			price	Transfer option price information object.
			paxPrice	Price per pax for this transfer option
		currencyCode	Currency code	
		value	Amount per pax	
			priceType	Price type. Values: <ul style="list-style-type: none">- Pax: price per pax- Vehicle: price per vehicle.
			supplement	Supplementobject. From 0 to n.
		currencyCode	Currency code	
		description	Supplement description	
		value	amount	

			Total	Total transfer price.
			currencyCode	Currency code
				Total transfer amount
			unitPrice	Price information object. From 1 to 2 items. Depends on priceType
			currencyCode	Currency code
				Amount per unit.
				Unit price type. Values: <ul style="list-style-type: none"> - Vehicle: in case this is a per vehicle price (Private transfers) - Pax: in case this is a per pax price (Shuttle transfers)
			serviceType	Service type. Values: <ul style="list-style-type: none"> - Private: Private vehicle transfer - Shuttle: shared vehicle transfer - Speedy Shuttle: shared vehicle transfer with less stops than a conventional transfer.
			Comments	Miscellaneous comments.
			Text	The value itself. See next note.
			Type	<p>Comment type. Values:</p> <ul style="list-style-type: none"> - “ Cancellation term ” : cancellation terms <u>by transfer</u>. The format is as follows: [Release – Percent%]. <p>For example: 7 – 5.0% , means cancelling a booking from 7 days before checkin date has a 5.0% of total booking amount penalty.</p> <p>Note: it is not possible to cancel a transfer online with a 100% percent penalty release (when it applies). You have to do it using the email, be aware of the fact the <u>booking cancellation request will remain “on request” and it is not confirmed</u>. Our staff will deal with it manually and contact your booking staff to confirm cancellation terms.</p> <ul style="list-style-type: none"> - “ Cancellation email ” : email to request a manual booking cancellation, useful when having a 100% cancellation penalty, see previous note. - “ Sales Commission percent ” : Commission applied - “ Sales Commission amount ” : Amount of the previous percent applied to the transfer price.

journeyDirection		Values: <ul style="list-style-type: none">- Going.- Return- Roundtrip
status		Values: <ul style="list-style-type: none">- CLOSED or CONFIRMED- OPEN
totalPrice		Total transfer price
	currencyCode	Currency code
	value	Total amount.