Steps to Setup Soapui

Version	Date	Author	Revised by
2.0	Dec – 2015	Bernat Carbonell	

DESCRIPTION

0. Download and install from site http://www.soapui.org

1. Go to File menu / New WSDL project

initial WSDL could be: http://test.xtravelsystem.com/public/v1_0rc1/commonsHandler?WSDL (later more can be added)

	testjumbo		
Initial WSDL http://test.xtravelsystem.cr	m/public/v1_0rc1/com Browse		
Create Requests 💌 Create sample requests	for all operations?		

2. Save project into file

Create Project			
Guardar en: 🛅 M	lis documento	\$	- 🖻 🖄 🎯 🗄
Delegaciones		🗀 IBM	🗀 LLEG Y SAL
🛅 ARCHIVOS Out	look	🗀 IIT	🗀 MAB
🗀 DB2LOG		🗀 inventari	🗀 Mis archivos
🗀 ETS		🗀 Jedox	🗀 Mis eBooks
🗀 ETS en COMUN_INF		🗀 jumbonline	🗀 Mis imágene
🗀 EXTRANET		🗀 keepass	🗀 Mis Webs
formacion		🗀 Liberar Sonyericsson P800_archivos 🗀 modulo-FSD	
🗀 fotoAGADIR		🗀 Liquidaciones	🗀 My Skype C
•	64 - C		
Nombre de archivo: testjumbo.xr		nl	
Archivos de tipo: XML Files (xml)	
			Guardar

3. Wait for WSDL to download/install



4. Go to left panel tree and choose method



soapUI 1.7.1 - 0 × Elle Iools Desktop Help Projects # ping - Request 1 or B X 🕨 늘 🗊 🖸 🗖 🔳 http://test.xtravelsystem.com/80/public/v1_0rc1/commonsHandler 78 + 10 E E LIVE2 kenv: Envelope mins: env="http://schemas.mlsoap.o B B LIVE3 B B LIVE4 \$ <soapenv:Envelope mains:soapenv="http://schemere.com/schemere.co XWI <soapenv:Header/> <env:Body E S LIVES <soapenv:Body> <ns0:pingResponse> B PREPROD
B TEST <typ:ping> <result> <PingRQ_1> <agencyStatus>ON</agencyStatus> 🗄 🗟 jumboclean <agencyCode>45</agencyCode> <enabledServices>HT</enabledServices> 🖨 🕒 testjumbo <brandCode>1</brandCode> <systemDate>2007-07-26709:55:35.6072< ia I CommonsHandlerBinding <point0fSaleId>1/point0fSaleId> <systemStatus>UP</systemStatus> i de getAirports i de getAreas </PingRQ_1> </result> </typ:ping> </ns0:pingResponse> 🗉 🧔 gelCities </soaper nv:Body> </env:Body> i getCitiesByArea
i getCountries </soapenv: Envelope> </env: Envelope> 🖶 🤹 GetEventsByArea 🗈 🤹 GetEventsByCity 🗄 🤹 getGeographicaMap 🕫 😂 GetOffers 🖶 👶 getProduct 🕀 🧔 getServices getVehiclesTypes
getVehiclesTypes
ping
12 Bequest 1 . 4 . # Request 1 🖻 👶 pingDispo SOAP Request Request Attachments (0) HTTP Headers (0) SDAP Respo Response Attachments (0) | HTTP Headers (6 1. response time: 83ms (623 bytes) 1:1 Request Properties Property Value Name Encoding Request 1 -UTF-8 ٠ Thu Jul 26 11:57:29 CEST 2007:INFO:importing operation getService Endpoint http://test.stravel. Thu Jul 26 11:57:29 CEST 2007:INFO:importing operation getVehiclesTypes Thu Jul 26 11:57:29 CEST 2007:INFO:importing operation ping Enable MTOM/I... false Useman Thu Jul 26 11:57:29 CEST 2007:INFO:importing operation pingDisp Thu Jul 26 11:58:28 CEST 2007:INFO:Got response for [CommonsH Password Ŧ monsHandlerBinding ping:Request 1] in 83ms (623 bytes) Domain 4 . Details Windows scapUI log http log jetty log

5. Fill params (in this case agencyCode, brandCode and pointOfSale) and click on Submit request button (the green arrow on the upper left corner). You should get then the results.

6. Add the rest of WSDL the same way:

http://test.xtravelsystem.com/public/v1_0rc1/basketHandler?WSDL http://test.xtravelsystem.com/public/v1_0rc1/hotelBookingHandler?WSDL http://test.xtravelsystem.com/public/v1_0rc1/transferBookingHandler?WSDL

Be aware that some tags are required even if empty. You can use a test – fail methodology or look at WSDL specification to send the correct requests.